



PU Hose/PVC Helix



Part No.	Ø ID (mm)	Min Wall thickness (mm)	Roll Length (m)	Wire Clip Ref
PUP38	38	0,8	30	3030250
PUP40	40	1	30	3030250
PUP45	45	1	30	3030269
PUP50	50	1	30	3030285
PUP60	60	1	30	3030306

Description:

Anti-Static Polyurethane hose reinforced with rigid PVC spiral helix and copper wire
 Inside surface perfectly smooth, outside corrugated
 Excellent flexibility
 High abrasion resistance
 Operating temperature -20°C to +80°C
 30m Coil

PU Hose/Steel Helix



Part No.	Ø ID (mm)	Min Wall thickness (mm)	Roll Length (m)	Wire Clip Ref
PURH38	38	1,5	10	3030250
PURH40	40	1,5	10	3030250
PURH45	45	1,5	10	3030269
PURH50	50	1,5	10	3030285
PURH60	60	1,5	10	3030306

Description:

Polyurethane hose reinforced with a copper covered steel helix
 Very high resistance to abrasions
 Excellent flexibility
 Smooth Bore
 Operating temperature -40°C to +80°C
 10m Coil

PVC Hose



Part No.	Ø ID (mm)	Min Wall thickness (mm)	Roll Length (m)
PAPVC19	19	25	30
PAPVC25	25	33	30
PAPVC31	31	38	30
PAPVC38	38	47	30
PAPVC50	50	60	30
PAPVC64	64	75	30
PAPVC75	75	88	30

Description:

Clear PVC Hose with a steel spiral helix
 Excellent Flexibility
 Inside & Outside Smooth
 Operating Temperature -10°C to +60°C
 30m Coil